

# AMPERES CL-902 / CL-904 / CL-908 / CL-912

## COLUMN SPEAKER 10W / 20W/ 40W/ 60W



VARIANTS :

**CL902** | 10W 100V LINE

**CL904** | 20W 100V LINE

**CL908** | 40W 100V LINE

**CL912** | 60W 100V LINE

### INTRODUCTION

Built ruggedly with aluminium die cast housing and available in 4 power rating of 10/ 20 / 40 and 60W 100V line with half or full power tapping.

Suitable for classrooms, hyper markets, mosques, ballroom, factories, passenger terminals, exhibition areas etc.



### TECHNICAL SPECIFICATIONS

	CL902	CL904	CL908	CL912
SPEAKER	2 x 2" corn	4 x 2" corn	8 x 2" corn	12 x 2" corn
Power rating	20W 100V	20W 100V	40W 100V	60W 100V
Line Voltage	100V	100V	100V	100V
Transformer Tapping (100V)	6W / 10W	10W / 20W	30W / 40W	50W / 60W
Primary Impedance (Ohm)	1.6k $\Omega$ / 1K $\Omega$	1k $\Omega$ / 500 $\Omega$	330 $\Omega$ / 250 $\Omega$	200 $\Omega$ / 166 $\Omega$
Sensitivity (1m / 1w)	87 $\pm$ 3dB	87 $\pm$ 3dB	88 $\pm$ 3dB	89 $\pm$ 3dB
Frequency Response	230 - 16 KHz			
Dimension (mm)	190 x 79 x 89	350 x 79 x 89	567 x 79 x 89	782 x 79 x 89
Material	Aluminium	Aluminium	Aluminium	Aluminium
Weight with Bracket (kg)	0.9 Kg	1.4 Kg	2.35 Kg	3.2k Kg
Speaker Unit		4 x 2"	8 x 2"	12 x 2"