

AMPERES DP-2212

120W x 2 MULTI CHANNEL PA AMPLIFIER



DP2000 Series are the new models of amplifiers which had been further refined to meet the market demands. DP2406 is a quad channel version with 60W 100W output per channel whereas **DP2212** shall be dual channel with output capacity of 120W 100V per channel.



FEATURES:

- ✓ Class D amplifier for wider frequency response
- ✓ Low power loss with higher efficiency circuiting
- ✓ Available in 2 x 120W or 4 x 60W 100W Line
- ✓ High ambient temperature operating condition
- ✓ AC and DC operation

TECHNICAL SPECIFICATIONS:

	DP-2212
Rating	2 x 120W 100V line
Operation Voltage	230 - 240V ac / 24V DC
Current Consumption	1.4 on 240V AC
Current (Load / Standby)	10.2A / 0.7A on 24V DC
Input	2 x XLR
Input Sensitivity	2.4Vrms Balanced
Outputs	100V, 70V, 30V
Frequency reponse	100Hz ~ 16kHz +/- 3 dB
Indicator	Power, Audio Input Level, Over temperature, Amplifier Faulty
Cooling system	Tri - speed Fan Control, Rear Fan Ventilation
Dimension (W x H x D)	482 x 88 x 335 mm
Weight	12 kg