

AMPERES DP-2406

60W x 4 MULTI CHANNEL PA AMPLIFIER



DP2000 Series are the new models of amplifiers which had been further refined to meet the market demands. **DP2406** is a quad channel version with 60W 100V output per channel whereas DP2212 shall be dual channel with output capacity of 120W 100V per channel.



FEATURES:

- ✓ Class D amplifier for wider frequency response
- ✓ Low power loss with higher efficiency circuiting
- ✓ Available in 2 x 120W or 4 x 60W 100V Line
- ✓ High ambient temperature operating condition
- ✓ AC and DC operation

TECHNICAL SPECIFICATIONS:

	DP-2406
Rating	4 x 60W 100 line
Operation Voltage	230 - 240V ac / 24V DC
Current Consumption	1.4 on 240V AC
Current (Load / Standby)	10.2A / 0.7A on 24V DC
Input	4 x XLR
Input Sensitivity	2.4Vrms Balanced
Outputs	100V, 70V, 30V
Frequency response	100Hz ~ 16kHz +/- 3 dB
Indicator	Power, Audio Input Level, Over temperature, Amplifier Faulty
Cooling system	Tri - speed Fan Control, Rear Fan Ventilation
Dimension (W x H x D)	482 x 88 x 335 mm
Weight	13.3 kg