

# AMPERES EP-1200

## RACK EMERGENCY PAGING PANEL



**EP1200** is enhanced version with RS485 data output, enabling the unit to be used together with iPX5150 IP client for LAN based PA system. Emergency paging and siren activation shall be available throughout the entire network from main rack. Other local features shall remain as EP1200, but with improved audio quality.

Extra feature available from EP1200A is the availability of a dry contact, which is activated whenever the unit is triggered. This allows connected to volume controller for overriding purpose.

We believe that this product shall be able to meet your demanding requirement with affordable pricing and uncompromised features and quality. Though it is rather simple in the installation works, a brief read through the manual is recommended and we are confident that you are getting a product of excellence.



### FEATURES

- ✓ RS485 Data Output
- ✓ Built in Siren Tone Generator
- ✓ Visual FIRE Indicator
- ✓ External Voice Message Activation
- ✓ Priority Front Panel Microphone Paging
- ✓ Aux Dry Contact for ALL CALL / E / M 24V Overriding Signal

### TECHNICAL SPECIFICATIONS

Power requirement	24V DC
Power consumption	3.5W
MICROPHONE	
Mic sensitivity	-72 dB Omni directional
Impedance	600 Ohm
Frequency response	300 - 8 KHz
SIREN	
Siren frequency	Continuous at 8 KHz
Siren duration	Continuous when activated
Siren activation	Front test switch / remote contact
Input channel	Pre-amplifier output, message recorder
Output level	Balanced line out (1.2V)
Priority sequence	Paging mic - siren - message - pre amp in
Indicators	Front FIRE with backlight illumination
Dimension (WxHxD)	482 x 88 x 180 mm
Weight	3.0 kg