

AMPERES MX-2222

12-INPUT MIXER PRE-AMPLIFIER



This compact 1-U pre-amplifier mixer features 6 mic, 4 BGM sources, chime and external line inputs and is suitable for any application, such as meeting, room, lecture theatre, hall of prayer and commercial fixed PA installation.

Its dual output feature can be used for uninterrupted paging setup, i.e. BGM and paging announcement. Adjustable priority muting level is available for paging announcement to override BGM and other lower priority sources. Adjusting it to minimum and the unit shall work like any other mixing unit and it comes with 12V phantom power supply for mic input 1 to 4.



FEATURES

- ✓ 12 inputs of mic, BGM sources, ext. Chime and mixer link
- ✓ Expandable to form more channels for larger setup
- ✓ Auto mic muting with adjustable mixing level for mic Ch. 1, 2, ext. chime and mixer link
- ✓ Priority muting with disable option for normal mixing mode
- ✓ Switchable phantom power for mic channel 1 to 4
- ✓ Dual output ; mixed line and BGM output for uninterrupted paging setup
- ✓ Independently adjustable BGM output level with balanced line
- ✓ Bass and treble tone control
- ✓ AC and DC operation for uninterrupted operation during power failure

TECHNICAL SPECIFICATIONS

Operating voltage	230 / 240V ac or 24V DC
Power consumption	2.4W on 240V ac / 100 mA on 24V DC
Input channels	6 x mic ; 4 x BGM ; Ext chime in ; mixer link
Input impedance	Mic : 600 Ohm
	BGM : 47 K Ohm unbalanced
	Chime input : 10 K Ohm unbalanced
	Mixer link : 600 Ohm balanced
Sensitivity	Mic : 0.775 mV
	BGM : 0.2V
	Chime : 0.7V
	Mixer : 0.7V
Output level	1.2V XLR balanced (mixed output)
	1.0V phone jack balanced (BGM output)
Output impedance	600 Ohm balanced
Controls	Mic channel ; chime ; mixer input
	Master mixed ; BGM ; Bass and treble controls
Phantom power	12V DC switchable at mic 1 to 4
Frequency response	175 - 15 KHz (+/-3 dB at 1 KHz) with low cut
S/N ratio	> 60 dB at 1 KHz
Dimensions (WxHxD)	482 x 44 x 180 mm
Weight	2.5 kg