

AMPERES SP-219 / SP-319

SOUND PROJECTOR SPEAKER



SP219 - 10W 100V SOUND PROJECTOR

SP319 - 10W x 2 100V LINE BI DIRECTIONAL SOUND PROJECTOR

INTRODUCTION

SP219 : UNIDIRECTIONAL SOUND PROJECTOR

SP219 is used when a more directional sound projection is required for areas such as at narrow corridors, tunnels, walkways, etc. It has aluminium body with metal grille and available with standard power rating of 10W 100V line. Mounting position can be either at wall or hanged from ceiling.

SP319 : BIDIRECTIONAL SOUND PROJECTOR

It is suitable for narrow corridors, or walkways that requires sound reproduction in two directional. Installing bi directional speakers may reduce the speaker counts and thus lowering installation and cabling costs.



TECHNICAL SPECIFICATIONS

	SP219	SP319
Power rating	10W 100V	
Power tapping (W)	Fixed at 10W	
Speaker	5"	2 x 5"
Primary impedance (Ohm)	1 K Ohm	
Secondary impedance (Ohm)	8 Ohm	
Frequency res (+/- 3dB @ 1KHz)	130 - 15 KHz	
SPL (1W / m @ 1 KHz)	91 dB	
Flare material	Aluminium body	
Grille / enclosure	Mild Steel	
Overall size (mm)	138 (diameter) x 205 (height)	
Weight	2.9 kg	3.5 kg
Color	White	